

BRUSH BLOCK ASSEMBLY BB






70 [2,75]

97 [3,82]

16 [0,62]

Technical drawing of a circular flange. The drawing shows concentric circles representing the flange's profile. Six mounting holes are distributed around the outer edge. Callouts provide the following specifications:

- Top callout: M8 X 1.25 X 14 DP  
(3) PLCS EQ SP DN  
210 [8.25] DIA B.C.
- Bottom callout: 5/16-18 UNC X 1.2 DP  
(3) PLCS EQ SP DN  
8.25 [210] DIA B.C.
- Right callout: Ø25 [Ø1,00] SHAFT BORE

SYN		REVISION		BY DATE		APV	
BY		DATE		  			
DRAWN		DATE					
LB		04/21/06					
CHECKED		DATE		222 WEST MEMORIAL ROAD (73114-2317) POST OFFICE BOX 26508 OKLAHOMA CITY, OK 73126-0508, U.S.A. PHONE: (405) 755-1600 FAX: (405) 755-8425			
MW		08/11/06					
APPROVED							
DRAWING REFERENCE		NUMBER		 			
DE-SURF ALL EDGES 0.015" MAX		STANDARD SHOP PRACTICES AND STANDARD SHOP TOLERANCES PER ASME Y14.5					
UNLESS OTHERWISE SPECIFIED		THIS DRAWING IS THE PROPERTY OF FITE CORPORATION. IT IS LOANED WITH THE UNDERSTANDING THAT IT MAY NOT BE REPRODUCED NOR MAY THE INFORMATION CONTAINED HEREIN BE USED FOR THE MAKING OF DRAWINGS OR FOR MANUFACTURING PURPOSES WITHOUT THE WRITTEN CONSENT OF FITE CORPORATION.					
GENERAL TOLERANCES ISO 2768-MK GEOMETRICAL SYMBOLS ISO 1031 SURFACES SEE LIST		SCALE		SIZE		DRAWING NO.	
		FULL		A1		GCDM24	
						SHEET NO. REV	
						1 OF 1	